

AT840/AT840P is ATCOM economic IP phone designed for executive users with very stably performance. Equiped with Lantiq Dual-core Voice engine, HD voice quality, BLF function and rich telephony features has been supported by AT840/AT840P, people can get an satisfied user experience in phone's setup / making calls / system administration. As a stable and firm terminal devices, all parts of AT840/AT840P are 100% veritable material.



- ▶ 128 x 64 pixels LCD with blacklit
- ▶ 9 programmable keys,4 soft keys
- ▶ Up to 4 SIP accounts
- ▶ HD voice, BLF function
- ▶ PoE support
- ▶ Multi-language
- ▶ Support Expansion modules (EX20B)



Concise appearance but Firm design

AT840/AT840P have inherited the advantage of ATCOM previous IP phone's design, it's a concise but firm phone, and absolutely with reliable performance.



HD Voice (handset, speaker phone)

AT840/AT840P support HD voice, enable calls with HD voice quality that make it seem like you're face-to-face communicating with the other party.



Easy Configuration

AT840/AT840P are supported Auto Provisioning by TFTP / FTP / HTTP / PnP,which make installer configure and maintain all phones easier and more conveniently.



Advanced expandability

AT840/AT840P support up to 5 Expansion module (EX20B), up to 100 additional keys



Compatible with a wide range of devices

AT840/AT840P have been validated by Asterisk and Broadsoft, can be compatible with a wide range of devices to meet customer's need.



Display Features

- ▶ LCD Display: 128 x 64 dot matrix LCD
- ▶ LCD Size:3.2"
- ▶ LCD Contrast:8 levels
- ▶ LCD Backlight:Yes

Install Option

- ▶ Desk Mount:Yes
- ▶ Wall Mount:No

Network Features

- ▶ IP Version:IPv4
- ▶ IP Assignment:Yes (Static / DHCP / PPPoE)
- ▷ DNS:Yes (Primary and Secondary DNS supported)
- ▶ HTTP:Yes
- ▷ SNTP Client:Yes
- ▶ VLAN (802.1Q):Yes
- ▶ QoS (DiffServ):Yes
- ▶ VPN:Yes (L2TP VPN supported)
- ▶ NAT Transverse:Yes (STUN mode)
- Security:Yes (SRTP / TLS supported)

Others

- ▶ Power Consumption:5W
- ▶ Operating Humidity:10 90%
- ▶ Operating Environment:0°C
 - 45°C (32°F 113°F)
- Dimension (Width x Depth x Height):23.8 x 11.8 x 18.5
- ▶ Weight:1.3Kg

SIP Features

- ▷ SIP Accounts:4
- ➤ SIP Compatibility:SIP v1 (RFC25 43),v2 (RFC3261), Asterisk,Broadsoft, ATCOM IP PBX

Keys Features

- ▶ Programmable Keys:9
- ▶ Features Keys:4 featureskeys (Mute, Headset, hands-free speakerphone, Message)
- ▶ Line LED Keys:4
- ▶ Volume Control Keys:2
- Context Sensitive Soft Keys:4
- ▶ Navigation Keys:5

Configuration and Management

- Plug & Play Configuration:Server based configuration,
- Manual Configuration:InternalWeb
 Configurator, Local (LCD based)
 network Configuration
- ► Auto Provision:TFTP / FTP / HTTP / PnP

Interface

- ▶ Ethernet Ports:2 10 / 100 Mbps
- ▶ RJ45 Extension Module Port:1 (Up to 5x Paper Extension Modules)
- PoE (Power over Ethernet):IEEE 802.3af Class 2 standard compliant
- ▶ Headset Jack:1 RJ9
- ▶ Handset Jack:1 RJ9
- ▶ Power adapter Jack:3.5mm,DC 12V,500mA

Audio Features

- ▶ Ringtones:10+2 user define
- ▶ Ringer Volume:8 levels + off
- ▶ Audio Codec:G.711(A/µ),G.722 (Wideband),G.726,G.729AB, iLBC, G.723

Software Features

- ▶ Phone Book (Entries):100
- Call Log Entries:100 Dialed calls
 +100 Answered Calls + 100
 Missed calls
- ▶ Conferncing:3 parties
- Music On Hold:Supplied by Host Service(PBX/SIP Server)
- Phone Basic Functions:
 One-Touch Speed Dial, RedialCall Forward, Call Waiting, Call
 Transfer, Call Hold, Call Return
 Mute, Auto answer, DND Call
 History: Dialed/Received/Missed
 Direct IP Call without SIP Proxy
 Hotline / Dail PlanSet Date/Time
 Manually or Automatically
- Phone Functions with IP PBX:
 Anonymous Call, Anonymous
 Call Rejection DND & Forward
 Synchronization Message Waiting
- ► Indicator (MWI) Voice Mail,
 Call Park, Call Pickup Intercom,
 Paging, Music on Hold Call
 Recording

