

AT810P/AT810

AT810/AT810P is ATCOM economic entry level IP phone designed for both Small and Medium business and residential, to replace traditional analog phone. Equiped with Lantiq Dual-core Voice engine, HD voice quality has been supported by AT810/AT810P, and also it's a desktop and Wall mountable IP phone, very easy to setup.





Concise appearance but Firm design

AT810/AT810P have inherited the advantage of ATCOM previous IP phone's design, it's a concise but firm phone, and absolutely with reliable performance.



HD Voice (handset, speaker phone)

AT810/AT810P support HD voice, enable calls with HD voice quality that make it seem like you're face-to-face with the other party.



Easy Configuration

AT810/AT810P are supported Auto Provisioning by TFTP / FTP / HTTP / PnP, which make installer configure and maintain all phones easier and more conveniently.



Compatible with a wide range of devices

AT810/AT810P have been validated by Asterisk and Broadsoft, can be compatible with a wide range of devices to meet customer's need.

atcom

AT810P/AT810

Display Features

- LCD Display:Segment LCD
- ▷ LCD Contrast:8 No
- LCD Backlight:Yes

Install Option

- Desk Mount:Yes
- ▷ Wall Mount:Yes

Network Features

- ▷ IP Version:IPv4
- ▷ IP Assignment:Yes (Static / DHCP / PPPoE)
- DNS:Yes (Primary and Secondary DNS supported)
- ▶ HTTP:Yes
- ▷ SNTP Client:Yes
- ▷ VLAN (802.1Q):Yes
- QoS (DiffServ):Yes
- VPN:Yes (L2TP VPN supported)
- NAT Transverse:
 Yes (STUN mode)
- Security:Yes (SRTP / TLS supported)

Others

- ▷ Ethernet Ports:2 10 / 100 Mbps
- PoE (Power over Ethernet):
 IEEE 802.3af Class 2 standard compliant
- ▷ Headset Jack:1 RJ9
- Handset Jack:1 RJ9
- Power adapter Jack:3.5mm,DC 12V,500mA

SIP Features

- ▷ SIP Accounts:1
- SIP Compatibility:SIP v1 (RFC2543), v2 (RFC3261),
 Asterisk,Broadsoft,
 ATCOM IP PBX

Keys Features

- ▷ Programmable Keys:0
- Features Keys:4 features keys
 (Mute, Headset, hands-free speakerphone, Message)
- ▷ Volume Control Keys:2

Configuration and Management

- Plug & Play Configuration:
 Server based configuration
- Manual Configuration:Internal
 Web Configurator, Local (LCD
 based) network Configuration
- ▷ Auto Provision:TFTP / FTP / HTTP / PnP

Interface

- ▷ Power Consumption:5W
- ▷ Operating Humidity:10 90%
- Operating Environment:0°C 45°C (32°F - 113°F)
- Dimension (Width x Depth x Height):
 16.3 x 11.8 x 18.5
- ▷ Weight:1.1Kg

Audio Features

- ▷ Ringtones:4+2 user define
- ▷ Ringer Volume:8 levels + off
- Audio Codec:G.711(A/µ),G.722
 (Wideband),G.726,G.729AB,
 iLBC,G.723

Software Features

- ▷ Phone Book (Entries):100
- Call Log Entries:50 Dialed calls
 + 50 Answered Calls + 50 Missed calls
- Conferncing:3 parties
- Music On Hold:Supplied by Host Service (PBX/SIP Server)
- Phone Basic Functions:One-Touch Speed Dial, RedialCall Forward, Call Waiting, Call Transfer, Call Hold, Call Return Mute, Auto answer, DND Call History: Dialed /Received/Missed Direct IP Call without SIP Proxy Hotline / Dail PlanSet Date/Time Manually or Automatically
- Phone Functions with IP PBX: Anonymous Call, Anonymous Call Rejection DND & Forward Synchronization Message Waiting Indicator (MWI) Voice Mail,Call Park, Call Pickup Intercom, Paging, Music on Hold Call Recording

